


Diagrams in the catalog show which accessories are possible for which presses.




Precision ram adjustment (DP)

As toggle presses do not achieve their maximum force until bottom dead center (BDC), adjusting the height of the press head by means of the threaded spindle is often too inaccurate. The precision ram adjustment enables the press pressure point to be precisely set directly at the ram. The scale on the adjustment ring enables the fine setting to be read off to 0.02 mm. The adjustment range is ± 1.5 mm. The precision ram adjustment is used when the utmost precision is required for the press depth. Ideal for prototype manufacture and serial production when accurate and easy adjustment within the tolerance range is required.



Micrometer stop (MICRO)

The micrometer stop is used with rack and pinion presses for high-precision assembly work or for when the tool has to be accurately positioned. This enables the press stroke length to be accurately adjusted to 0.01 mm



Return travel lock (HS)

The return travel lock for toggle and rack and pinion presses is an effective contribution to quality assurance during production. The return travel lock rules out partial strokes and therefore incomplete operations. Forming, assembly and joining operations are always reliably and completely executed, as the return stroke of the press is blocked on the downward stroke. The interlock is only released and the lever can only be returned when the stroke is complete. The Quick-Release mechanism enables this inhibit to be released and jammed parts to be removed in any position. The Quick-Release is automatically deactivated when the lever is returned.






Table bore (TB)

The bottom part of the tool can be mounted in the centric table bore. Fixing is by means of a transverse screw in all models up to 80 mm throat. The table bore enables the tool to be changed quickly and reduces set-up time. The alignment accuracy of the ram bore with the table bore is < 0.05 mm.



stroke counter (Z)

A rapid overview of the number of items produced can be obtained with the five-digit stroke counter. The number of items can be reset.

